

<p>Package Contents</p> <p>Main system unit (codec) The New eCam PTZ camera EVC microphone array IR remote control Power supply Cables Warranty card Quick guide</p>	<p>Communications</p> <p>H.323, SIP standards, SIP TLS 64Kbps~4Mbps RJ45 network LAN (10/100/1000) Manual bandwidth settings</p>	<p>Camera/The new eCam PTZ:</p> <p>Pan/Tilt/Zoom camera 2-megapixel CMOS sensor 18X total zoom ±130° pan; +90°/-25° tilt Field of view (H): 72° Field of view (V): 43° Field of view (Diagonal): 82°</p>
<p>People Video Resolutions</p> <p>HD1080p (1920 x 1080) HD720p (1280 x 720) 480p (848 x 480) 4CIF (704 x 576) CIF (352 x 288) SIF (352 x 240) All resolutions at 30fps</p>	<p>Content Video Resolutions Supported resolutions:</p> <p>HD1080p (1920 x 1080) WXGA+ (1680 x 1050) SXGA (1280 x 1024) WXGA (1280 x 768) HD720p (1280 x 720) XGA (1024 x 768) SVGA (800 x 600) D1 (720 x 480) VGA (640 x 480) Output resolutions: HD1080p (1920 x 1080) up to 30fps</p>	<p>Video Standards</p> <p>H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261 H.239 dual video streams BFCP content sharing</p>
<p>Video Features</p> <p>3D Denoise</p>	<p>Video Inputs</p> <p>EVC eCam camera VGA DVI (HDMI)</p>	<p>Video Outputs</p> <p>HDMI VGA</p>
<p>Audio Standards</p> <p>G.711, G.722, G.728, G.722.1, G.722.1C licensed from Polycom®</p>	<p>Audio Features</p> <p>Automatic gain control (AGC) Advanced noise reduction Acoustic echo cancellation (AEC)</p>	<p>Audio Inputs</p> <p>EVC microphone daisy chain up to 4 DVI (HDMI) Line-in (3.5 mm)</p>

<p>Audio Outputs</p> <p>HDMI Line-out (3.5 mm)</p>	<p>Other Supported Standards</p> <p>H.224, H.225, H.245, H.281, H.323 Annex Q, H.460 SRTP</p>	<p>User Interface</p> <p>Multiple layout styles User-friendly OSD (supports 22 languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Spanish, Swedish, Thai, Turkish) Display/edit site name</p>
<p>Network</p> <p>10/100/1000Mbps NAT/firewall traversal High Efficiency Lost Packet Recovery (HELPeR™) API support via Telnet Wake-on-LAN (WOL) support IPv4 and IPv6 support Network Test QoS</p>	<p>Security</p> <p>AES (Advanced Encryption Standard) function (128-bit) Password protection for system settings Password protection for remote system management</p>	<p>Web Management Tool</p> <p>Remote management through the Web Live monitoring via the Web Firmware update via Ethernet/Internet Phonebook download/upload/edit Restore system settings Export call history</p>

Value-Added Features	Power Supply	Environmental Data
<p>Meeting recording In meeting and offline recording Save directly to USB flash drive Supports screen re-layout during playback Playback and file conversion via VCPlayer software (.mov/.mp4 format) EZMeetup software/App 30-day for free trial Connect with H.264 video codec Receive resolution up to full HD 1080p 30fps Transmit resolution up to full HD 1080p 30fps Compatible with firmware later v10.06 Support content sharing, capture and recording EZDraw App Compatible with firmware later v10.12 Import .JPG, .PNG, .GIF and .BMP files Export .PNG files A maximum of 10 devices can be connected Speed dialing via hot keys (10 sets) Camera presets (100 positions) Network Time Protocol (NTP) ScreenShare support VCLink support SnapShot Group Calling Supports SIP voice calls</p>	<p>AC 100V~240V, 50/60Hz Consumption: EIAJ 12V, 4A</p>	<p>Operation temperature: 0°C~40°C Operation humidity: 20%~80% Storage temperature: -20°C~60°C Storage humidity: 20%~80%</p>

<p>Physical Characteristics</p> <p>Package dimensions: 376 x 300 x 243 mm</p> <p>Package weight: 6.99kg (15.41lbs)</p> <p>Main system (codec): 320 x 262.7 x 37.2 mm</p> <p>The New eCam PTZ: 180 x 144 x 184 mm</p> <p>EVC microphone array: 131.9 x 118.6 x 25.5 mm</p>	<p>Warranty</p> <p>3-year standard warranty can extend up to 02 years by register online.</p>	
--	--	--